

11. THE KS-54A CAMERA INSTALLATION AS DESCRIBED ON MODIFICATION DRAWING 0000211, TO BE REMOVED PRIOR TO CIVIL CERTIFICATION OF THE AIRCRAFT (IF INSTALLED).

12. STEEL STAMP ENGINE NAME PLATE "T.C. E-269."

13. CHANGE M.A.A. PLATE (RH DOORPOST) AS FOLLOWS: OBLITERATE L-19E AND ADD 305C OR OBLITERATE L-19A AND ADD 305D, AS APPLICABLE. (305M)

14. REMOVE CARBURETOR ALTERNATE AIR FILTER IF INSTALLED. THIS ALTERNATE AIR FILTER WAS INSTALLED BY THE MILITARY PER TM 55-1510-202-34/9 OR T.O. 11-1-513 AND WILL NOT MEET THE FAA REQUIREMENTS FOR TEMPERATURE RISE OF ALTERNATE AIR. REMOVE HOSE ADAPTER FROM CARBURETOR AIR BOX AND SEAL 2-7/16 DIA HOLE WITH A .032 2024-T3 METAL PLATE. DO NOT DISTURB SPRING LOADED ALTERNATE AIR DOOR.

15. INSTALL 12305-223-1 ROTATING BEACON PLACARD "CAUTION - DO NOT OPERATE ROTATING BEACON DURING INSTRUMENT FLIGHT" ON LOWER EDGE OF INSTRUMENT PANEL BELOW CLOCK.

16. THE AMOUNT OF BAGGAGE THAT CAN BE CARRIED IS DEPENDENT UPON THE RADIO EQUIPMENT INSTALLED. IF SPACE IS AVAILABLE AND THE CG LIMITS ARE NOT EXCEEDED, A MAXIMUM OF 100 LBS MAY BE CARRIED IN THE BAGGAGE COMPARTMENT. 0610370 PLACARD "NO BAGGAGE ALLOWED" OR 0610070 PLACARD "MAX BAGGAGE 100 LBS, FOR ADDITIONAL LOADING INSTRUCTIONS SEE WEIGHT AND BALANCE DATA" SHOULD BE EXISTING IN THE AIRCRAFT. THE CORRECT PLACARD IS DETERMINED AFTER THE AIRCRAFT IS WEIGHED.

THIS AIRCRAFT WILL BE LICENSED UNDER FAA (CAA) AIRCRAFT SPECIFICATION 5A5 FOR MODEL 305C OR 305D, AS APPLICABLE.

METHOD OF MARKING OPTIONAL (TAPE, PAINT, DECAL, ETC), MAY BE APPLIED ON OUTSIDE OF GLASS. SEE CAM 3.756.

METHOD OF MARKING OPTIONAL - STENCIL, DECAL, METALCAL, SCOTCHCAL OR DATAK, ETC. SEE CAM 3.755.

MAY BE LOCALLY MANUFACTURED (\*\* IS APPLICABLE)

DO NOT SCALE PRINT  
BREAK ALL SHARP EDGES  
A/R AS REQ'D  
CES - XXXX - CESSNA SPEC.  
NUMBER  
S - XXX OR CNRUK - CESSNA  
STD. NO.  
CXXXXX - CESSNA CRAFTED  
NO.  
X - APPROX. SIZE AND  
LOCATION  
OF INK STAMP PART MARKING  
S - APPROX. EQUAL SPACES ±  
HOLE TOL. PER \_\_\_\_\_  
FINISH CODE PER \_\_\_\_\_  
PROCESS PER \_\_\_\_\_  
EDGES